

STYLEX

Model: NYC Two seater with arm

*Refer to P.2 for model variations

Disassembly and Recycling Document

Disassembly Time: 10min / No Special Training Required

Tools Required

safety glasses
phillips screwdriver



Breakdown Steps


1. Turn the chair on its back to reveal the metal legs. locate the weld tabs that are bolted to the frame. Using a phillips heads screw driver or drill, remove all 8 screws from the frame, releasing the wood frame from the legs (figure A1).




3. Keeping the frame on its back, unscrew the bolts holding the seat cushions to the wooden frame. Remove the cushions from frame.



3. To remove the back seat cushions push the cushions upwards. This will slide the cushions off of the bracket that is holding them in place.



4. Finally remove the bracket and shoulder screw from the frame and back seat cushion so that they can be recycled (figure D1 and D2).



- Wood frame
- Material:
Foam, plywood, upholstery



- Back cushion x2
- Material:
Foam, plywood, upholstery



- Seat cushion x2
- Material:
Foam, plywood, upholstery



- Leg Frame
- Material: Steel, aluminum



-Metal Swivel
-Material: Steel

-Shoulder screw x4
-Bracket x4
-Wood Screw x8
-Washer x8
-Philips truss-head screw x16 (1/4 20)
Material: Steel